

METHOD OF AND APPARATUS FOR MANUFACTURING PRODUCTS

BACKGROUND OF THE INVENTION

Field of the Invention:

5 The present invention relates to a method of and an apparatus for manufacturing products in a plurality of types having different specifications.

Description of the Related Art:

10 Film manufacturing apparatus, for example, operate by drawing a film blank from a film roll, cutting the film blank transversely and longitudinally into a plurality of films, winding the films around respective cores thereby to produce rolls, and then supplying the rolls to a next process.

15 The rolls thus manufactured are available in a number of types having different specifications including different core diameters, different roll widths, different film lengths, different winding directions (rolls with inner coated surfaces and rolls with outer coated surfaces), etc.
20 The film manufacturing apparatus are designed to produce a plurality of types of products in a mixed fashion to meet recent demands for the production of products in many types and in small quantities.

25 It has been desired to supply the film manufacturing apparatus with cores in a suitable component form efficiently and accurately depending on the types of rolls to be manufactured.

Heretofore, product manufacturing apparatus for manufacturing various products by supplying components in different types to intermediate products are designed to check whether such components are defective or not.

5 However, the product manufacturing apparatus are supposed to be supplied with components in appropriate types, and do not perform a matching process for determining whether supplied components match intermediate products or not. Therefore, if some failure is discovered in the process of manufacturing products on the product manufacturing apparatus, then the feed line thereof needs to be shut down, adversely affecting the overall manufacturing process.

10 Film rolls supplied to the film manufacturing apparatus may possibly contain defective regions and roll-to-roll joints. Positional information representing such defective regions and roll-to-roll joints are supplied from a management apparatus to the film manufacturing apparatus, in which films corresponding to those defective regions and roll-to-roll joints are removed.

15
20 In the film manufacturing apparatus, since films are cut in transverse and longitudinal directions and fed successively, desired films cannot be removed unless the sequence in which the films are fed is accurately recognized. Particularly in a system arranged to supply products to a single feed line from a plurality of feed
25 paths, it is extremely difficult to accurately determine which products are to be removed.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a method of and an apparatus for manufacturing products in a plurality of types having different specifications efficiently by supplying appropriate components to intermediate products.

Another object of the present invention is to provide a method of and an apparatus for manufacturing a plurality of products so as to be able to supply the products in a desired sequence to a feed line.

Still another object of the present invention is to provide a method of and an apparatus for manufacturing products so as to be able to easily and reliably process the manufactured products.

The above and other objects, features, and advantages of the present invention will become more apparent from the following description when taken in conjunction with the accompanying drawings in which preferred embodiments of the present invention are shown by way of illustrative example.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic plan view of a roll production line to which a method of and an apparatus for manufacturing products according to the present invention are applied;

FIG. 2 is a schematic perspective view of a film processing and cutting machine which serves as part of the

roll production line shown in FIG. 1;

FIG. 3 is a plan view of the film processing and cutting machine shown in FIG. 2 and a core supply apparatus for supplying cores to the film processing and cutting machine;

FIG. 4 is a block diagram of a control circuit of the film processing and cutting machine and the core supply apparatus shown in FIG. 3;

FIG. 5 is a diagram illustrative of tracking data stored in a tracking data memory of the control circuit shown in FIG. 4;

FIGS. 6 through 8 show a flowchart of an operation sequence of a core supply process;

FIG. 9 is a perspective view of the film processing and cutting machine and a roll feed mechanism which serve as part of the roll production line shown in FIG. 1;

FIG. 10 is a block diagram of a control circuit of the film processing and feeding apparatus shown in FIG. 9;

FIG. 11 is a view showing memory areas corresponding to various regions of the film processing and feeding apparatus shown in FIG. 9;

FIG. 12 is a diagram illustrative of tracking data stored in a tracking data memory of the control circuit shown in FIG. 10;

FIG. 13 is a perspective view illustrative of block numbers and slit numbers which are tracking data set on a web;

FIG. 14 is a view illustrative of a manufacturing pattern of products in the film processing and cutting machine in a state shown in FIGS. 1 and 2;

FIG. 15 is a view illustrative of a manufacturing pattern of products in the film processing and cutting machine in a state shown in FIG. 9;

FIG. 16 is a diagram showing the manner in which the tracking data shown in FIG. 12 are rewritten;

FIG. 17 is a flowchart of a processing sequence of a first transfer unit in the roll feed mechanism shown in FIG. 9; and

FIG. 18 is a flowchart of a processing sequence of a second transfer unit in the roll feed mechanism shown in FIG. 9.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 schematically shows in plan a roll production line 100 to which a method of and an apparatus for manufacturing products according to the present invention are applied. The roll production line 100 is basically constructed of a core supply apparatus 1308 for supplying cores 28 of a given length and diameter, a film processing and cutting machine 12 for cutting an elongate raw film (raw web) 16 drawn from a film roll 14 into films and winding the films around cores 28 thereby to produce a plurality of rolls 30a through 30d, and a roll feed mechanism (feed line) 1200 for feeding the produced rolls 30a through 30d. The

film processing and cutting machine 12 and the roll feed mechanism 1200 jointly make up a film processing and feeding apparatus 1100.

FIG. 2 schematically shows in perspective a film processing and cutting machine 12 according to a first embodiment of the present invention. The film processing and cutting machine 12 has a plurality of rotary cutters 48 for cutting an elongate film 16 into films having given widths and a cutting means (not shown) for cutting the elongate film 16 to given lengths. The elongate film 16 is unwound from a photosensitive roll (hereinafter referred to as "film roll 14") of a PET (polyethylene terephthalate) film, a TAC (triacetylcellulose) film, a PEN (polyethylene naphthalate) film, or a photographic printing paper used as a base. In a film winding apparatus 10, the severed films 16 are wound around respective cores 28 supplied from the core supply apparatus 1308, thus producing a plurality of rolls 30a through 30d, 30a' through 30d'. Edges 32 of excessive elongate films are produced at opposite sides of the elongate film 16.

The film processing and cutting machine 12 is capable of producing a plurality of types of rolls 30a through 30d, 30a' through 30d' according to a production plan.

Specifically, the film winding apparatus 10 has a first winding unit 1102A and a second winding unit 1102B that are spaced from each other by a given distance in the direction in which the elongate films 16 are drawn from the film roll

14. The first winding unit 1102A and the second winding unit 1102B produce the rolls 30a, 30c or 30a', 30c' and the rolls 30b, 30d or 30b', 30d'. The rolls 30a through 30d and the rolls 30a' through 30d' differ from each other as to the direction in which the elongate films 16 are wound. The rolls 30a through 30d and the rolls 30a' through 30d' are available in various types dependent on combinations of widths of the elongate films 16, diameters of the cores 28, and directions in which the elongate films 16 are wound.

A region of the first winding unit 1102A for manufacturing the rolls 30a, 30c will be referred to as an A axis, a region of the first winding unit 1102A for manufacturing the rolls 30a', 30c' as an A' axis, a region of the second winding unit 1102B for manufacturing the rolls 30b, 30d as a B axis, and a region of the second winding unit 1102B for manufacturing the rolls 30b', 30d' as a B' axis.

Alongside of the film winding apparatus 10 of the film processing and cutting machine 12, there are disposed feed mechanisms 1300, 1302 for supplying cores 28 to the first winding unit 1102A and feed mechanisms 1304, 1306 for supplying cores 28 to the second winding unit 1102B. The feed mechanism 1300 supplies cores 28 to the A axis of the first winding unit 1102A, the feed mechanism 1302 supplies cores 28 to the A' axis of the first winding unit 1102A, the feed mechanism 1304 supplies cores 28 to the B axis of the second winding unit 1102B, and the feed mechanism 1306

supplies cores 28 to the B' axis of the second winding unit 1102B.

FIG. 3 illustrates in plan the film processing and cutting machine 12 shown in FIG. 2 and the core supply apparatus 1308 for supplying cores 28 to the film processing and cutting machine 12.

The core supply apparatus 1308 comprises two feed mechanisms 1310, 1312 for supplying a plurality of cores 28 that have been cut to given lengths depending on the widths of the rolls 30a through 30d and the rolls 30a' through 30d' which are manufactured by the film processing and cutting machine 12, and a core loader 1314 for sorting out cores 28 according to length and diameter. The core loader 1314 and the feed mechanisms 1302, 1306 disposed close to the film processing and cutting machine 12 are connected to each other by feed mechanisms 1316, 1318.

The core loader 1314 has a feed mechanism 1320 connected to the feed mechanism 1310 and a feed mechanism 1322 connected to the feed mechanism 1312. A discharger 1324 for discharging cores 28 that have been determined as defective is disposed between the feed mechanisms 1320, 1322. The core loader 1314 also has feed mechanisms 1326, 1328 extending transversely across the feed mechanisms 1320, 1322 and connected to the feed mechanisms 1316, 1318, respectively. Above the discharger 1324, there is disposed a core feed robot (not shown) for loading cores 28 fed to the feed mechanisms 1320, 1322 into the feed mechanisms

1326, 1328 or the discharger (discharging means) 1324. The core loader 1314 has a measuring means, to be described later on, for measuring the length and diameter of each of supplied cores 28.

5 FIG. 4 shows in block form a control circuit (comparing means) 1330, according to the first embodiment, of the film processing and cutting machine 12 and the core supply apparatus 1308 which are constructed as described above. As shown in FIG. 4, the control circuit 1330 is controlled by a controller 1331, and a management computer 1010 is connected to the control circuit 1330 through a process control computer 1008. The management computer 1010 manages an overall production process of the roll production line 100 including the film processing and cutting machine 12 and the core supply apparatus 1308. The process control computer 1008 is supplied with production plan data from the management computer 1010.

10
15
20 The production plan data are stored via an input/output unit 1332 of the control circuit 1330 into a production plan data memory (required component information holding means) 1334. The production plan data stored in the production plan data memory 1334 include required component information representing widths of rolls 30a through 30d, 30a' through 30d' produced by the film processing and cutting machine 12 and diameters of cores 28, and data representing winding directions of rolls 30a through 30d, 30a' through 30d'.

25 The control circuit 1330 has a core data memory

(supplied component information holding means) 1336 for storing core data supplied from the core supply apparatus 1308. Core data as supplied component information include data representing diameters and lengths of cores 28 that are cut to given lengths and supplied by the core supply apparatus 1308, and are supplied from the core supply apparatus 1308 via an input/output unit 1338.

The control circuit 1330 has a tracking data memory (tracking data holding means) 1340 for storing tracking data of cores 28 which are fed from the core loader 1314 of the core supply apparatus 1308 to the film winding apparatus 10 of the film processing and cutting machine 12. As shown in FIG. 5, the tracking data include length and diameter data of cores 28 that have been fed and winding direction data of rolls 30a through 30d, 30a' through 30d' that have been supplied. The tracking data are stored in memory areas ME1 through ME10 which are established in association with the feed mechanisms 1326, 1328, 1316, 1318, 1302, 1300, 1306, 1304, the first winding unit 1102A, and the second winding unit 1102B to which cores 28 are supplied.

The core loader 1314 has a core length measuring unit (component measuring means) 1342 for measuring lengths of cores 28 supplied to the feed mechanisms 1320, 1322 and a core diameter measuring unit (component measuring means) 1344 for measuring diameters of those cores 28. Measured component information obtained by these measuring units is supplied via an input/output unit 1346 to the controller

1331. A plurality of core passage detectors 1348 for detecting passage of cores 28 and copying tracking data stored in the tracking data memory 1340 are disposed in a feed path extending from the core loader 1314 to the film winding apparatus 10. Core detecting signals from the core passage detectors 1348 are supplied via the input/output unit 1346 to the controller 1331.

The roll production line 100 according to the first embodiment to which the method and apparatus according to the present invention are applied is basically constructed as described above. Operation of the roll production line 100 will be described below.

Prior to a process of cutting the film roll 14 with the film processing and cutting machine 12, the management computer 1010 supplies production plan data relative to a type of rolls 30a through 30d, 30a' through 30d' via the process control computer 1008 to the control circuit 1330. The control circuit 1330 stores the supplied production plan data into the production plan data memory 1334, and controls the film winding apparatus 10 of the film processing and cutting machine 12 via the input/output unit 1338 according to the production plan data. For example, according to the production plan data representing the width of rolls 30a through 30d, 30a' through 30d', the diameter of cores 28, and the winding direction of the elongate film 16, the control circuit 1330 adjusts the location of the cutting means (not shown) and determines which of the first winding

unit 1102A and the second winding unit 1102B is to manufacture rolls 30a' through 30d'.

5 After the film processing apparatus 10 has been adjusted as described above, the control circuit 1330 instructs the core supply apparatus 1308 to supply cores 28 to be used according to the production plan data. A process of supplying cores 28 will be described below with reference to a flowchart shown in FIGS. 6 through 8.

10 In the flowchart, A#1 and A#3 represent core length data and core diameter data of cores 28 required for rolls 30a through 30d, 30a' through 30d' to be manufactured by the first winding unit 1102A of the film winding apparatus 10 shown in FIG. 3, B#2 and B#4 represent core length data and core diameter data of cores 28 required for rolls 30a through 30d, 30a' through 30d' to be manufactured by the second winding unit 1102B of the film winding apparatus 10, and S1C/V and S2C/V represent core length data and core diameter data of cores 28 supplied to the feed mechanisms 1320, 1322 of the core supply apparatus 1308 shown in FIG. 3.

20 The controller 1331 reads the data A#1 of a core 28 required to manufacture rolls 30a, 30a' in the first winding unit 1102A from the production plan data memory 1334, reads the data S1C/V of a core 28 fed to the feed mechanism 1320 of the core loader 1314 in the core supply apparatus 1308
25 from the core data memory 1336, and compares these data A#1, S1C/V with each other in step S1.

W3
A2

10014507-152401

If A#1 = S1C/V, indicating that a core 28 is fed to the feed mechanism 1320 of the core loader 1314, then the length and diameter of the core 28 supplied to the feed mechanism 28 are measured in step S2. The length of a core 28 is measured by the core length measuring unit 1342 in the feed mechanism 1320, and supplied to the controller 1331 via the input unit 1346. The diameter of a core 28 is measured by the core diameter measuring unit 1344 in the core feed robot (not shown) for feeding the core 28 when the core 28 is gripped by the core feed robot, and supplied to the controller 1331 via the input unit 1346.

If the measured results agree with the data S1C/V relative to the core 28 in step S3, then the core feed robot loads the core 28 supplied to the feed mechanism 1320 into the feed mechanism 1326 corresponding to the A axis (associated with the first winding unit 1102A) of the film winding apparatus 10 in step S4. When the core 28 is loaded into the feed mechanism 1326, control goes to a process of supplying cores 28 to rolls 30b, 30b'.

If the measured results do not agree with the data S1C/V relative to the desired core 28 in step S3, then the controller 1331 determines that the data suffer some defect or the core supply apparatus 1308 fails to supply the core 28. The core feed robot loads the core 28 supplied to the feed mechanism 1320 into the discharger 1324 in step S5. When the core 28 is loaded into the discharger 1324, a process for a next core 28 may be repeated, or the core

supply apparatus 1308 may be shut off, allowing the operator to confirm the situation.

When the suitable core 28 is loaded into the feed mechanism 1326 in step S4, the controller 1331 generates tracking data which comprise the core length data and core diameter data of the core 28 and the winding direction data, from the production plan data memory 1334, of a roll 30a or 30a' to which the core 28 is supplied, and stores the generated tracking data in the memory area ME1 of the tracking data memory 1340 corresponding to the feed mechanism 1326.

If A#1 \neq S1C/V in step S1, then the controller 1331 reads the data S2C/V of a core 28 fed to the feed mechanism 1322 of the core loader 1314 in the core supply apparatus 1308 from the core data memory 1336, and compares the data S2C/V with the data A#1 in step S6. Thereafter, as with steps S2 through S5, the core 28 supplied to the feed mechanism 1322 is loaded into the feed mechanism 1326 associated with the A axis of the film winding apparatus 10 or loaded as an inappropriate core 28 into the discharger 1324 in steps S7 through S10.

Then, the controller 1331 reads the data B#2 of a core 28 required to manufacture rolls 30b, 30b' in the second winding unit 1102B from the production plan data memory 1334, reads the data S1C/V of a core 28 fed to the feed mechanism 1320 of the core loader 1314 in the core supply apparatus 1308 from the core data memory 1336, and compares

these data B#2, S1C/V with each other in step S11.

Thereafter, as with steps S2 through S5, the core 28 supplied to the feed mechanism 1320 is loaded into the feed mechanism 1328 associated with the B axis of the film winding apparatus 10 or loaded as an inappropriate core 28 into the discharger 1324 in steps S12 through S15.

The memory area ME2 of the tracking data memory 1340 corresponding to the feed mechanism 1328 stores the core length data and core diameter data of the core 28 supplied to a roll 30b or 30b', and the winding direction data of the roll 30b or 30b'.

If B#2 \neq S1C/V in step S11, then the controller 1331 reads the data S2C/V of a core 28 fed to the feed mechanism 1322 of the core loader 1314 in the core supply apparatus 1308 from the core data memory 1336, and compares the data S2C/V with the data B#2 in step S16. Thereafter, as with steps S12 through S15, the core 28 supplied to the feed mechanism 1322 is loaded into the feed mechanism 1328 associated with the B axis of the film winding apparatus 10 or loaded as an inappropriate core 28 into the discharger 1324 in steps S17 through S20.

When the core 28 corresponding to the roll 30a or 30a' is supplied to the feed mechanism 1326, the core 28 corresponding to the roll 30b or 30b' is supplied to the feed mechanism 1328, and these cores 28 are fed to the next feed mechanisms 1316, 1318, cores 28 are supplied to the roll 30c or 30c' and the roll 30d or 30d' in steps S21

through S40.

5 The cores 28 supplied from the core supply apparatus 1308 are fed together with tracking data added thereto to the film processing and cutting mechanism 12. Specifically, when the core passage detector 1348 detects the cores 28 fed from the feed mechanisms 1326, 1328 of the core loader 1314 to the feed mechanisms 1316, 1318, the controller 1331 copies the tracking data stored in the memory areas ME1, ME2 to the memory areas ME3, ME4 corresponding to the feed mechanisms 1316, 1318.

10 Similarly, as the cores 28 are fed from the feed mechanisms 1316, 1318 to the feed mechanisms 1302, 1306, the feed mechanisms 1300, 1304, the first winding unit 1102A, and the second winding unit 1102B, the tracking data are also copied from the memory areas ME3, ME4 successively to the memory areas ME5, ME7, the memory areas ME6, ME8, and the memory areas ME9, ME10.

20 By thus moving the tracking data together with the cores 28, it is possible to transfer the information of the cores 28 with the tracking data, thus preventing inappropriate cores 28 from being supplied to the film processing and cutting machine 12 in advance.

25 To the tracking data, there are added data of the winding directions of supplied rolls 30a through 30d, 30a' through 30d' to be able to determine which of the A and B axes or the A' and B' axes the cores 28 in the feed mechanisms 1302, 1306 are to be fed to.

10014607-191401
5 A roll production line 100 according to a second embodiment of the present invention to which the method and apparatus according to the present invention are applied will be described below. Those parts of the second embodiment which are identical to those of the first embodiment are denoted by identical reference characters, and will not be described in detail below.

FIG. 9 schematically shows in perspective a film processing and feeding apparatus 100 according to the second embodiment. In the second embodiment shown in FIG. 9, the rolls 30b, 30d are wound in the first winding unit 1102A and the rolls 30a, 30c are wound in the second winding unit 1102B in the film processing and cutting machine 12.

The first winding unit 1102A and the second winding unit 1102B have a first feed unit 1104A and a second feed unit 1104B for feeding the wound rolls 30a through 30d to the roll feed mechanism 1200.

20 The roll feed mechanism 1200 comprises a first feed unit 1106A and a second feed unit 1106B (feed means) for receiving rolls 30a through 30d from the first feed unit 1104A and the second feed unit 1104B and feeding the received rolls 30a through 30d, and a main feed unit 1108 for arranging the rolls 30a through 30d received from the first feed unit 1106A and the second feed unit 1106B into an array and feeding the arrayed rolls 30a through 30d to a
25 next process.

Over the main feed unit 1108 connected to the first

feed unit 1106A and the second feed unit 1106B, there are disposed a first transfer unit 1110A and a second transfer unit 1110B (transfer means) for transferring the rolls 30a through 30d onto pallets 1109 on the main feed unit 1108.

5 On the main feed unit 1108, there are disposed, successively from the first transfer unit 1110A and the second transfer unit 1110B, a turntable 1112 for changing the direction of the rolls 30a through 30d, a roll discharger 1114 for discharging specified ones of the rolls 30a through 30d, buffers 1116, 1118 for adjusting the speed at which the rolls 30a through 30d are fed, and a roll transfer unit 1120 for transferring the rolls 30a through 30d to a next process.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199

information of rolls 30a through 30d fed by the film processing and feeding apparatus 1100, and a controller (product selecting means) 1506 for receiving, via an input unit 1503, passage information of rolls 30a through 30d detected by the roll passage detectors 1122A, 1122B and 1124A, 1124B, 1126a through 1126f, and controlling the film processing and feeding apparatus 1100 via an input/output unit 1504 according to the passage information and the tracking data.

The process control computer 1008 to which the management computer 1010 is connected is connected to the control circuit 1500 through an input/output unit 1508. Based on a production plan, the management computer 1010 supplies the control circuit 1500 with cutting information for rolls 30a through 30d.

FIG. 11 shows the relationship between memory areas ME11 through ME22 of the tracking data memory 1502 for storing tracking data and various regions corresponding to the memory areas ME11 through ME22. The memory areas ME11, ME12 hold address information of rolls 30a through 30d in the first winding unit 1102A and the second winding unit 1102B. The memory areas ME13, ME14 hold address information of rolls 30a through 30d in the first feed unit 1106A and the second feed unit 1106B. The memory areas ME15, ME16 hold address information of rolls 30a through 30d in the first transfer unit 1110A and the second transfer unit 1110B. The memory areas ME17 through ME22 hold address

information of rolls 30a through 30d in loading positions
for the rolls 30a through 30d in the main feed unit 1108.

FIG. 12 shows an arrangement of tracking data stored in
each of the memory areas ME11 through ME22 of the tracking
data memory 1502. The tracking data have a header a1 and
slit data a2. The header a1 includes block numbers (final
passage block numbers) and slit numbers (final passage slit
numbers) which represent final address information of rolls
30a through 30d that have passed respective regions of the
film processing and feeding apparatus 1100 which correspond
to the memory areas ME11 through ME22. The slit data a2
include block numbers (intra-areal block numbers) and slit
numbers (intra-areal slit numbers) which represent address
information of rolls 30a through 30d that are presently
positioned in the regions of the film processing and feeding
apparatus 1100 which correspond to the memory areas ME11
through ME22.

The block numbers and the slit numbers are defined as
shown in FIG. 13. The block numbers are numbers
representing rolls 30a through 30d that are produced by
cutting the film roll 14 in a direction perpendicular to the
longitudinal direction of the film roll 14. The slit
numbers are numbers representing rolls 30a through 30d that
are produced by cutting the film roll 14 in the longitudinal
direction thereof with the rotary cutters 48. In the second
embodiment, the block numbers are successively set as block
#1, block #2,... in the longitudinal direction of the

elongate film 16 as it is drawn from the film roll 14. The slit numbers are successively set as slit #1, slit #2,... in the transverse direction of the elongate film 16 from the side where rolls 30a through 30d are delivered.

5 The film processing and feeding apparatus 1100 according to the second embodiment and the control circuit 1500 thereof are basically constructed as described above. Operation of the film processing and feeding apparatus 1100 and the control circuit 1500 will be described below.

10 Prior to a process of cutting the film roll 14 with the film processing and cutting machine 12, the management computer 1010 supplies production information relative to a type of rolls 30a through 30d based on a production plan via the process control computer 1008 to the control circuit 1500. The control circuit 1500 controls the film processing and cutting machine 12 of the film processing and feeding apparatus 1100 via the input/output unit 1504 according to the supplied production information. For example, according to the production information representing the width of
20 rolls 30a through 30d and the diameter of cores 28, the control circuit 1500 adjusts the location of the rotary cutters 48 and determines which of the first winding unit 1102A and the second winding unit 1102B is to manufacture rolls 30a through 30d.

25 In the second embodiment, the locations of winding mechanisms 1103a through 1103d, 1103e through 1103h (see FIGS. 14 and 15) of the first winding unit 1102A and the

second winding unit 1102B with respect to the direction indicated by the arrows and the location of the rotary cutters 48 are adjusted depending on the different diameters of the cores 28, the different widths of the rolls 30a through 30d, and the different winding directions (indicative of whether a roll with an inner coated surface or a roll with an outer coated surface is to be produced) of the elongate film 16.

In FIG. 14, the distances between the winding mechanisms 1103b, 1103c and between the winding mechanisms 1103f, 1103g cannot be reduced beyond a certain width because of a mechanical interference. Therefore, the width of the roll 30b wound by the winding mechanism 1103e, 1103f of the second winding unit 1102B corresponding to the region between the winding mechanisms 1103b, 1103c is limited to or more than a certain value. Similarly, the width of the roll 30c wound by the winding mechanisms 1103c, 1103d of the first winding unit 1102A corresponding to the region between the winding mechanisms 1103f, 1103g is also limited to or more than a certain value. As a result, the first winding unit 1102A and the second winding unit 1102B have a choice of two patterns where the wide rolls 30b, 30c are positioned at its center, as shown in FIGS. 14 and 15.

After one of the patterns shown in FIGS. 14 and 15 is thus selected and the film processing apparatus 12 has been adjusted, the rolls 30a through 30d start being manufactured. The elongate film 16 drawn from the film roll

14 is cut by the rotary cutters 48 into films, which are wound around respective cores 28 in the first winding unit 1102A and the second winding unit 1102B, thus producing rolls 30a through 30d.

5 When the rolls 30a through 30d are produced in the first winding unit 1102A and the second winding unit 1102B, the memory area ME11 and the memory area ME12 store block numbers and slit numbers as the slit data a2.

10 For example, if the rolls 30a through 30d are manufactured according to the pattern shown in FIG. 14, the memory area ME11 stores block #1 as an intra-areal block number and slit #1 and slit #3 as intra-areal slit numbers, and the memory area ME12 stores block #1 as an intra-areal block number and slit #2 and slit #4 as intra-areal slit numbers.

15 If the rolls 30a through 30d are manufactured according to the pattern shown in FIG. 15, the memory area ME11 stores block #1 as an intra-areal block number and slit #2 and slit #4 as intra-areal slit numbers, and the memory area ME12 stores block #1 as an intra-areal block number and slit #1 and slit #3 as intra-areal slit numbers.

20 For manufacturing the rolls 30a through 30d according to the pattern shown in FIG. 14, when the first feed unit 1104A is actuated to feed a core 30a of block #1, slit #1 to the first feed unit 1106A, the core passage detector 1122A detects passage of the roll 30a. Based on a detected signal representing the roll 30a, the controller 1506 stores

tracking data of block #1, slit #1 as the slit data a2 in the memory area ME13 corresponding to the first feed unit 1106A. The controller 1506 also stores the tracking data of block #1, slit #1 of the roll 30a which have been stored as the slit data a2 up to present, as a final passage block number and a final passage slit number as the header a1 in the memory area ME11 which corresponds to the first feed unit 1104A to which the roll 30a is fed. FIG. 16 schematically shows such a process of rewriting the tracking data.

Similarly, when a core 30b of block #1, slit #2 is fed from the second feed unit 1104B to the second feed unit 1106B, tracking data of block #1, slit #2 are stored as the slit data a2 in the memory area ME14, and tracking data of block #1, slit #2 are stored as the header a1 in the memory area ME12.

The above process of processing the tracking data with the controller 1506 is also performed as the rolls 30a through 30d are fed from the film processing and cutting mechanism 12 to various portions of the film feed mechanism 1200.

Since the rolls 30a through 30d are fed from the film processing and cutting mechanism 12 in either one of the patterns shown in FIGS. 14 and 15, the first transfer unit 1110A and the second transfer unit 1110B are required to detect the sequence in which the rolls 30a through 30d are fed, and selectively supply the rolls 30a through 30d to the

main feed unit 1108.

A process of supplying the rolls 30a through 30d to the main feed unit 1108 in the order of slits will be described below with reference to flowcharts shown in FIGS. 17 and 18.

5 FIG. 17 shows a process in the first transfer unit 1110A. If the controller 1506 detects that the rolls 30a through 30d are supplied to the main transfer unit 1110A in step S1A and the pallet 1109 arrives at a given area in the main feed unit 1108 in step S2A, then the controller 1506 reads the tracking data stored in the memory area ME15. If the intra-areal slit number of the slit data a2 is slit #1 in step S3A, then the controller 1506 transfers the rolls 30a through 30d in the first transfer unit 1110A to the pallet 1109 in step S4A. In this case, the rolls 30a through 30d are supplied according to the pattern shown in FIG. 14.

10
15
20
25
Then, the controller 1506 reads again the tracking data stored in the memory area ME15. If the intra-areal slit number of the slit data a2 is slit #3 in step S8A, then the controller 1506 reads the tracking data stored in the memory area ME16 corresponding to the second transfer unit 1110B. If the final passage slit number of the header a1 of the tracking data is slit #2 in step S9A, then since it is determined that the rolls 30a through 30d of slit #2 have already been supplied from the second transfer unit 1110B to the pallet 1109, the controller 1506 transfers the rolls 30a through 30d of slit #3 to the pallet 1109 in step S10A.

10044607-40947007
104725-421401

5 If the intra-areal slit number of the slit data a2 stored in the memory area ME15 corresponding to the first transfer unit 1110A is slit #2 in step S5A, then the controller 1506 reads the tracking data stored in the memory area ME16 corresponding to the second transfer unit 1110B. After the rolls 30a through 30d whose final passage slit number of the header a1 is slit #1 are detected as being supplied to the main feed unit 1108 in step S6A, the controller 1506 transfers the rolls 30a through 30d of slit #2 to the pallet 1109 in step S7A. In this case, the rolls 30a through 30d are supplied according to the pattern shown in FIG. 15.

20 Then, the controller 1506 reads again the tracking data stored in the memory area ME15. If the intra-areal slit number of the slit data a2 is slit #4 in step S11A, then the controller 1506 reads the tracking data stored in the memory area ME16 corresponding to the second transfer unit 1110B. If the final passage slit number of the header a1 of the tracking data is slit #3 in step S12A, then since it is determined that the rolls 30a through 30d of slit #3 have already been supplied from the second transfer unit 1110B to the pallet 1109, the controller 1506 transfers the rolls 30a through 30d of slit #4 to the pallet 1109 in step S13A.

25 FIG. 18 shows a process in the second transfer unit 1110B. The second transfer unit 1110B performs the same process as the first transfer unit 1110A in steps S1B through S13B which correspond to steps S1A through S13A.

10044507 " 231401
The main feed unit 1108 is thus supplied with the rolls 30a through 30d in the order of slits #1 through #4 which are manufactured from the film roll 14. Similarly, the main feed unit 1108 is supplied with the rolls 30a through 30d in the order of slits which have a next block number.

The rolls 30a through 30d transferred to the main feed unit 1108 are changed in orientation when necessary by the turntable 1112, and thereafter reach the roll discharger 1114. Inasmuch as the rolls 30a through 30d are supplied in a desired sequence to the roll discharger 1114, the operator can reliably discharge the rolls 30a through 30d as desired without errors. The rolls 30a through 30d are then delivered through the buffers 1116, 1118 and the roll transfer unit 1120 to a next process.

As described above, rolls 30a through 30d supplied via the first transfer unit 1110A and the second transfer unit 1110B are rearranged in the order of slits and supplied to the main feed unit 1108. In the second embodiment described above, the rolls 30a through 30d supplied via the first feed unit 1104A and the second feed unit 1104B are selected by the first transfer unit 1110A and the second transfer unit 1110B and supplied to the main feed unit 1108. However, rolls 30a through 30d from three or more feed units may be supplied in a desired sequence to the main feed unit 1108 and arranged therein.

Although certain preferred embodiments of the present invention have been shown and described in detail, it should

be understood that various changes and modifications may be made therein without departing from the scope of the appended claims.

10014607 . 121401